


## NBS-3502

2-section anodised aluminium telescopic mast

50mm O.D. base

2.955 metres - Packed

5.6 metres - Extended



### Specifications

Construction	Clear anodised aluminium telescopic sections with section stop guides and passivated D-locking clips
Number of Sections	2
Retracted Height	2.955 metres / 9.69 ft
Extended Height	5.60 metres / 18.37 ft
Weight - excl. D-clips	4.0 kg / 8.82 lbs
Wind Load rating - Max.	160 kph / 99mph - with each section guy wire supported
Top section load rating	3.5kg / 7.71 lbs
Max. surface area	0.2m <sup>2</sup>
Base Section Dimension	O.D: 50mm / 1.97"
2nd Section Dimensions	O.D: 45mm / 1.77"
Supplied Accessories	1 x gold passivated section D-clips

### Required Accessories - order quantity separately to suit 3/4 configuration

Guy Wire - High strength nylon <i>Single units, order by quantity required either 3 or 4 at each section For stainless steel see NBS-GW series</i>	NBS-GR5 - 5 metre guy wire for base section NBS-GR10 - 10 metre guy wire for top section
Anodised Aluminium Guy Rings - free rotating <i>single unit required - per mast</i>	NBS-AGR51 - Suits 50mm O.D. bottom section NBS-AGR46 - Suits 45mm O.D. top section

### Optional Accessories - order separately to suit configuration

Mount Bases	NBS-50WStand - drive-on/underwheel static stand NBS-50TStand - drive-on/underwheel tilt stand NBS-50TBMount - tow-bar socket mount NBS-BS50 - static flat roof/ground stand
Antenna/Equipment mounts	1.3m top accessory mount tube 45mm O.D., includes 'D' locking clip - <u>Enquire Directly for SKU</u>