

NBS-BJACK Series

Single or Dual action bottle jacks for NBS-Tiltmast

For lifting and lowering NBS-Tiltmast arm



NBS-BJACK - single action

Please note: Image is for illustration purposes only, model may differ in colour/appearance from supplied.



NBS-BJACK-2 - dual action

Please note: Image is for illustration purposes only, model may differ in colour/appearance from supplied.

Specifications

Construction	Painted toughened steel outer main body with internal piston, toughened steel fixing brackets, adjustable pressure valve, single or dual action pump with detachable handle.
SKU	NBS-BJACK Single action NBS-BJACK-2 Dual action
Suitable Masts	Suits NBS-Tiltmast direct fitment, onto jack mount bracket on main assembly and piston fitment bracket on tilt arm
Weight	3.1 - 5.2kg
Action type	Single action - extends with downstroke only Dual action - extends with up and downstroke
Load rating - Max.	8 Ton
Installation hardware	1 x jack to bracket mount pin - included 1 x piston to bracket mount pin - included
Installation	<p>Connect your bottle jack with the tilt arm in the horizontal orientation. This will mean you will not have to extend the piston until extension required. Install the lower fixing pin through the mount bracket and bottle jack and then attach the piston to the tilt arm fitment bracket. Ensure pins are inserted and secure prior to extending the jack.</p> <p>Please note: Our NBS-BJACK series should only be used for lifting and controlled lowering your NBS-Tiltmast. Retainment of raised or lowered positions should be maintained with supports or the securing bolts supplied. the NBS-BJACK series should be removed when not lifting/lowering to maintain functionality/movement.</p>