

## **Section 4: Mast Accessories**

0351571203

Sales@nbsmasts.com.au mbsmasts.com.au

## **NBS-TEM**

Heavy-duty galvanised, top equipment mount assembly for NBS-Tiltmast Requires 88.9mm SHS extension





Specifications	
Construction	Fully-galvanised internally reinforced steel mount assembly and equipment mount tube
Suitable mast	NBS-Tiltmast with 88.9mm SHS extension
Overall Dimensions	Overall height: 850mm Equipment mount tube: 594mm x 48mm OD x 3.2mm W.T. Insert depth: 150mm
Weight	7.2kg
Mounting holes	21mm O.D.
Mounting hardware	1 x M20 x 140mm bolt + washer/nut
Installation requirements	<ul> <li>NBS-Tiltmast (order separate)</li> <li>88.9mm SHS extension</li> <li>21mm drill bit + drill</li> <li>Adjustable spanners for securing bolt</li> <li>Install your 88.9mm SHS tube into your NBS-Tiltmast first, then slide NBS-2865-8 onto the end of your 88.9mm SHS, drill the securing hole through the 88.9mm SHS tube and secure using supplied M20 bolt/washer/nut.</li> </ul>
Bolt on same face as tilt-arm bolt - Horizontal to ground 88.9mm SHS extension can be any length as p requirements	





Side view



Updated 22nd September 2023 Specifications are subject to change without prior notice © G-tech Communications Services Pty Ltd